

PR-HS30W-IP

IP ONVIF 30W Outdoor horn speaker

Power meets resilience with this 30W outdoor IP horn speaker. Delivering a robust sound output of 120dB, it is perfect for larger outdoor spaces, providing loud and clear audio while withstanding tough weather conditions.



Built In
30W
Amplifier

120
dB

IP67
Protection
rating

MAIN FEATURES

- PR-HS30W-IP IP ONVIF 30W Outdoor horn speaker
- Amplifier: Built-in 30W Amplifier
- Max SPL: 120dB
- Frequency Response: 350Hz~8KHz
- Installation: Wall/Ceiling Mount
- Power: PoE / DC12V ~2.5Amp / 24V~1.5Amp
- Power Consumption: 30W Max
- Operation Temperature: -30-60°C
- Protection Rate: IP67
- Dimensions: 285*205*290mm (W x H x D)
- Net Weight: ~2Kg
- Power supply not included



SPECIFICATIONS

Speaker	
Max SPL	120dB
Frequency Response	350Hz~8KHz
Audio	
Usage	Real-Time Audio Broadcast / Up to 10 pre-loaded files (Triggered by API)
Codec	OPUS 48kHz, MP3 44.1kHz, G.722 ADPCM 16kHz, G.711 PCMU 8kHz, G.711 PCMA 8kHz
Amplifier	
Amplifier	Built-in 30W Amplifier
Network	
Protocols	SIP, ONVIF, HTTP, HTTPS, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NTP, Multicast
VoIP	2 SIP Accounts SIP Direct IP Call RTP Multicast
Security	Password protection, IP address filtering, Digest authentication, User access log
Onvif	Profile S
Interface	10/100 Base-TX, RJ45
GENERAL	
Power	PoE / DC12V ~2.5Amp / 24V~1.5Amp
Power Consumption	30W Max
Protection Rate	IP67
Installation	Wall/Ceiling Mount
Dimensions	285*205*290mm (W x H x D)
Net Weight	~2Kg
Operation Temperature	-30-60°C